

zwena connect HF P350 3K

ZWENA CONNECT P

neva
lux

350 x 82 mm



zwena connect HF P350 3K

ZWENA CONNECT P

Technical Data

IDENTIFICATION		Mounting height	< 4 m	With emergency light	No	
Source	woocommerce	Nevalux sensor technology	Smartlink, BT SIG Mesh	Direct/indirect ratio separately controllable	No	
Product status	Normal	With light sensor	Yes	With program-controlled lighting control	Yes	
Manufacturer	Nevalux	CONNECTIVITY				
DIMENSIONS		With radio network control	Yes	Constant light output control	Yes	
Dimensions Ø × H	350 x 82 mm	LIGHTING TECHNOLOGY				
Suspension length	1500 mm	Colour temperature	3000 K	HOUSING & MATERIAL		
ELECTRICAL		LED colour deviation	SDCM3	Protection class (IP)	IP20	
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	Protection class	I	
Power	18 W	Illuminant	LED	Ambient temperature	-20...45 °C	
Replaceable driver	Yes	Luminous flux	1700 lm (Down 1200, Up 500)	Housing material	Aluminum	
Type of wiring	Suitable for through wiring	Beam angle	Down 95°, Up 100°	Cover material	Microprismatic acrylic glass	
LED rated current	450 mA	Luminaire luminous efficacy	94 lm/W	Mounting type	Ceiling pendant	
SENSOR TECHNOLOGY		Glare value	UGR < 18	Colour	White	
Sensor technology	High frequency	SCOPE OF DELIVERY & WARRANTY				
With motion detector	Yes	Manufacturer warranty				5 years
Detection angle	360°	CERTIFICATES & EPREL				
Radial range	Ø 8 m (50 m²)	EPREL energy efficiency class				F
Tangential range	Ø 8 m (50 m²)	DALI dimming				Yes

zwena connect HF P350 3K

ZWENA CONNECT P

Illustrations


MOUNTING HEIGHT

< 4 m BEREICH
--

zwena connect HF P350 3K

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221753	Emergency Package 1h (50V/1.5W/Compact/PS)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222057

Typ

zwena connect HF P350 3K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss