

elani P3200 TW

ELANI

neva
lux

3140 x 60 x 80 mm



elani P3200 TW

ELANI

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable		Yes
Source	woocommerce	Colour temperature	3000...5600 K	Constant light output control		Yes
Product status	Normal	LED colour deviation	SDCM3			
Manufacturer	Nevalux	Colour rendering index	80-89	HOUSING & MATERIAL		
DIMENSIONS		Illuminant	Yes, LED-System	Protection class (IP)	IP20	
Dimensions L x W x H	3140 x 60 x 80 mm	Luminous flux	12560 lm (Down 8164, Up 4396)	Protection class	II	
Suspension length	2000 mm	Beam angle	Down 105°, Up 115°	Ambient temperature	-20...45 °C	
ELECTRICAL		Luminaire luminous efficacy	129 lm/W	Housing material	Aluminium	
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 22	Cover material	Acrylic glass opal	
Power	97 W	LIFETIME		Mounting type	Ceiling pendant	
Replaceable driver	Yes	LED lifespan (25 °C)	70000 h	Colour	Aluminium	
SENSOR TECHNOLOGY		SETTINGS		SCOPE OF DELIVERY & WARRANTY		
With motion detector	No	DALI dimming	Yes	Manufacturer warranty	5 years	
Nevalux sensor technology	DALI 2	With emergency light	No	CERTIFICATES & EPREL		
With light sensor	No	Suitable for light band configuration	Yes	EPREL energy efficiency class	D	

elani P3200 TW

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221102	elani Diffusor 3200 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221397	elani Color RAL_NCS_3200	Other
 221997	elani WM-Set 3B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221114

Typ

elani P3200 TW

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss