

aluna connect LS C910 3K

ALUNA

neva
lux

910 x 118 mm



aluna connect LS C910 3K

ALUNA

Technical Data

IDENTIFICATION		CONNECTIVITY			
Source	woocommerce	With radio network control	Yes	With emergency light	No
Product status	Normal	LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	No
Manufacturer	Nevalux	Colour temperature	3000 K	With program-controlled lighting control	Yes
DIMENSIONS		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Dimensions Ø × H	910 x 118 mm	Colour rendering index	80-89	Protection class (IP)	IP20
ELECTRICAL		Illuminant	LED	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	9800 lm (Down 8430, Up 1370)	Ambient temperature	-20...45 °C
Power	78 W	Beam angle	105°	Housing material	Steel
Replaceable driver	Yes	Luminaire luminous efficacy	125 lm/W	Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	Glare value	UGR < 21	Mounting type	Ceiling surface-mounted
SENSOR TECHNOLOGY		LIFETIME		Colour	White
With motion detector	No	LED lifespan (25 °C)	70000 h	SCOPE OF DELIVERY & WARRANTY	
Nevalux sensor technology	Smartlink, BT SIG Mesh	SETTINGS		Manufacturer warranty	5 years
With light sensor	Yes	DALI dimming	Yes	CERTIFICATES & EPREL	
				EPREL energy efficiency class	D

aluna connect LS C910 3K

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221846	aluna Color RAL_NCS_0910	Other
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222020

Typ

aluna connect LS C910 3K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss