

RS PRO P3 SP neutralweiss

P-SERIE

neva
lux

400 x 142 mm



RS PRO P3 SP neutralweiss

P-SERIE

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Source	woocommerce	Measured luminous flux 360°	2188 lm	Impact resistance	IK03
Product status	Normal	Colour temperature	4000 K	Protection class (IP)	IP54
Manufacturer	Nevalux	Illuminant	LED cannot be replaced	Protection class	II
DIMENSIONS		Base	without	Ambient temperature	from -10 up to 40 °C
Dimensions Ø × H	400 x 142 mm	LED cooling system	Passive Thermo Control	Housing material	Plastic
ELECTRICAL		Soft light start	Yes	Cover material	Plastic, opal
Mains connection	220 – 240 V / 50 – 60 Hz	LIFETIME		Mounting location	wall\nceiling
Power	17,8 W	LED lifetime max. °C	50000 h	Colour	white
SENSOR TECHNOLOGY		LED lifetime L70B50 25°C	> 60000 h	SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	Luminous flux decline per LM80	L80B10	Manufacturer warranty	5 years
CONNECTIVITY		SETTINGS		CERTIFICATES & EPREL	
Networking via	Cable	Main light adjustable	No	Certificates	DEKRA

RS PRO P3 SP neutralweiss

P-SERIE

Accessories

ORDERING INFORMATION

Art.-Nr. 221813

Typ **RS PRO P3 SP neutralweiss**

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss