

nyota C400 4K 90

NYOTA CONNECT

neva
lux

- The powerful high-bay luminaire nevalux nyota is designed for the illumination of rooms with high ceilings. With its 32,000 lumens, this luminaire is the ideal choice for all types of industrial, exhibition and logistics halls. Thanks to the DALI driver integrated as standard, the light intensity can be ideally adapted to the respective conditions. The IP65 water jet protection combined with the IK09 shock resistance rating make this luminaire almost indestructible.

400 x 137 mm



nyota C400 4K 90

NYOTA CONNECT

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No
Source	woocommerce	LIGHTING TECHNOLOGY			HOUSING & MATERIAL		
Product status	Normal	Colour temperature	4000 K		Impact resistance	IK09	
Manufacturer	Nevalux	LED colour deviation	SDCM3		Protection class (IP)	IP65	
DIMENSIONS		Colour rendering index	80-89		Protection class	I	
Dimensions Ø × H	400 x 137 mm	Illuminant	LED		Ambient temperature	-20...50 °C	
ELECTRICAL		Luminous flux	32000 lm		Housing material	Steel	
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	90°		Cover material	Lens transparent	
Power	200 W	Luminaire luminous efficacy	160 lm/W		Mounting type	Ceiling / Wall / Pendant	
Replaceable driver	Yes	Glare value	UGR < 22		Colour	Black	
Maximum number of luminaires per circuit breaker	C10: 5x, C13: 6x, C16: 8x, C25: 12x, B10: 3x, B13: 4x, B16: 5x, B25: 7x	LIFETIME			SCOPE OF DELIVERY & WARRANTY		
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h		Manufacturer warranty	5 years	
With motion detector	No	SETTINGS			CERTIFICATES & EPREL		
Nevalux sensor technology	DALI 2	DALI dimming	Yes		EPREL energy efficiency class	C	

nyota C400 4K 90

NYOTA CONNECT

Accessories

ORDERING INFORMATION

Art.-Nr. 221585

Typ nyota C400 4K 90

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss