

imani B1500 HO 4K DALI

IMANI CONNECT

neva
lux

- The universal trunking insert imani from nevalux is designed for professional refurbishment of existing trunking with T5 or T8 fluorescent tubes. The luminaire uses the existing trunking installation including existing through-wiring. Old light modules can be replaced with new modules easily, quickly and without tools. The insert fits most trunking systems available on the market.

1525 x 65 x 30 mm



imani B1500 HO 4K DALI

IMANI CONNECT

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions L x W x H	1525 x 65 x 30 mm
PU1 net weight	1.9
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	65 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
LED rated current	350 mA
Maximum number of luminaires per circuit breaker	C10: 21x, C16: 35x, B10: 13x , B16: 21x
SENSOR TECHNOLOGY	
With motion detector	No

Nevalux sensor technology	DALI 2
With light sensor	No
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	8264 lm
Beam angle	105°
Luminaire luminous efficacy	127 lm/W
Glare value	UGR < 24
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes
With emergency light	No

Suitable for light band configuration	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP40
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Diffusor opal
Mounting type	Use in continuous row
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	D

imani B1500 HO 4K DALI

IMANI CONNECT

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220688	Emergency Package 1h (250V/3.5W)	Emergency lighting
 221477	imani APG1500	Surface mount housing

ORDERING INFORMATION

Art.-Nr.

221495

Typ

imani B1500 HO 4K DALI

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss