

RS PRO S30 SC Multipack (5 pcs.) Multipack

neva
lux**SENSOR-SWITCHED LED INDOOR LIGHT**

EAN 4007841079727

350 x 83 mm



RS PRO S30 SC Multipack (5 pcs.) Multipack

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079727

Technical Data

IDENTIFICATION	
PU1 EAN	4007841079727
Material number	110082940
SAP designation	LED INNENLEUCHTE RS PRO S30 SC WW PM.MP5
Product name data sheet	RS PRO S30 SC Multipack (5 pcs.) Multipack
Product category	Sensor-switched LED indoor light
Discount group	DL
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel
DIMENSIONS	
Dimensions Ø × H	350 x 83 mm
PU1 net weight	6.2
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	25,7 W
Own consumption	0,39 W
B10 fuse (pcs)	36
B16 fuse (pcs)	58
C10 fuse (pcs)	61
C16 fuse (pcs)	97
Maximum inrush current	16,5 A
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No

Radial range	Ø 10 m (79 m²)
Tangential range	Ø 10 m (79 m²)
Mounting height	2 – 4 m
Optimal mounting height	2,8 m
Nevalux sensor technology	BT SIG Mesh
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master
Networking via	Bluetooth Mesh
Slave mode adjustable	Yes
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	2615 lm
Colour temperature	3000 K
LED colour deviation	SDCM3
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
LIFETIME	
LED lifetime max. °C	55000 h
Luminous flux decline per LM80	L80B50
LED lifetime per IEC 62717 L70	100.000 h
LED lifetime per IEC 62717 L80	74.000 h
LED lifetime per IES TM-21 L70	>60.000 h
LED lifetime per IES TM-21 L80	>60.000 h
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	Yes
Base light function detail	LED effect light

Base light function time	1-60 min
Main light adjustable	Yes
Functions	Neighbouring group function Presence function Group parameterisation Manual ON / ON-OFF Connection to central battery systems Motions sensor DIM function Adjustable fade time when switching on and off Free selection of the light value in a luminaire group Normal / test mode Orientation light Presence detector logic Encrypted communication
Settings via	Bluetooth Mesh Smartphone
With remote control	No
Twilight setting teach	Yes
Base light function in percent	7 – 100 %
Base light function percent from	7
Base light function percent to	100
HOUSING & MATERIAL	
Impact resistance	IK07
Protection class (IP)	IP20
Protection class	II
Ambient temperature	from -20 up to 40 °C
Housing material	Aluminium
Mounting location	ceiling wall
Application location	Indoors
Mounting type	Surface wiring
Material	Aluminium
Application room	changing room kitchenette Indoors outdoors WC / washroom stairwell function room / ancillary room corridor / aisle
Colour	Silver
Protection class ceiling	IP20
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
House number sheet included	No


RS PRO S30 SC Multipack (5 pcs.) Multipack

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079727

Illustrations

TECHNICAL DRAWINGS



350 x 83 mm

MOUNTING HEIGHT


2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
---------------------------------------	-------------------------------------	----------------------------------

RS PRO S30 SC Multipack (5 pcs.) Multipack


EAN 4007841079727

SENSOR-SWITCHED LED INDOOR LIGHT

Wiring Diagrams

WIRING DIAGRAM 1

Slave/wireless master interconnection circuit diagram

WIRING DIAGRAM 2


Master/master interconnection circuit diagram

RS PRO S30 SC Multipack (5 pcs.) Multipack

EAN 4007841079727

SENSOR-SWITCHED LED INDOOR LIGHT

Highlights



Including STEINEL LED system



Intelligent LED cooling system



Optional basic lighting level 10 %



Optional basic lighting level 10 - 20%



Wireless interconnection



High-quality aluminium

RS PRO S30 SC Multipack (5 pcs.) Multipack

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841079727

Accessories

ORDERING INFORMATION	
Art.-Nr.	079727
EAN	4007841079727
Typ	RS PRO S30 SC Multipack (5 pcs.) Multipack
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	