

elani C2400 3K

ELANI

neva
lux

2400 x 60 x 80 mm



elani C2400 3K

ELANI

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Suitable for light band configuration	Yes
Source	woocommerce	Colour temperature	3000 K		
Product status	Normal	LED colour deviation	SDCM3	HOUSING & MATERIAL	
Manufacturer	Nevalux	Colour rendering index	80-89	Protection class (IP)	IP20
DIMENSIONS		Illuminant	Yes, LED-System	Protection class	II
Dimensions L x W x H	2400 x 60 x 80 mm	Luminous flux	6720 lm	Ambient temperature	-20...45 °C
ELECTRICAL		Beam angle	105°	Housing material	Aluminium
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	112 lm/W	Cover material	Acrylic glass opal
Power	60 W	Glare value	UGR < 24	Mounting type	Ceiling / wall surface-mounted
Replaceable driver	Yes	LIFETIME		Colour	Aluminium
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		SETTINGS		Manufacturer warranty	5 years
With motion detector	No	DALI dimming	Yes	CERTIFICATES & EPREL	
Nevalux sensor technology	DALI 2	With emergency light	No	EPREL energy efficiency class	E
With light sensor	No				

elani C2400 3K

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221396	elani Color RAL_NCS_2400	Other
 221107	elani Link	Coupler/connector straight
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221136

Typ

elani C2400 3K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss