

fayola MF2 On-Off/Phasecut D2W

FAYOLA MF2

neva
lux

90 x 83 mm



fayola MF2 On-Off/Phasecut D2W

FAYOLA MF2

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
Source	woocommerce	With motion detector	No	DALI dimming	No
Product status	Normal	Nevalux sensor technology	On / Off	HOUSING & MATERIAL	
Manufacturer	Nevalux	LIGHTING TECHNOLOGY		Protection class (IP)	IP20
DIMENSIONS		Colour temperature	1800...3000 K	Protection class	II
Dimensions Ø × H	90 x 83 mm	LED colour deviation	SDCM3	Ambient temperature	-20...40 °C
Drill hole	75 mm	Colour rendering index	80-89	Housing material	Aluminum
ELECTRICAL		Illuminant	LED	Cover material	Reflector aluminium
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	470 lm	Mounting type	In-ceiling installation
Power	8 W	Beam angle	60°	Colour	White
Replaceable driver	Yes	Luminaire luminous efficacy	59 lm/W	SCOPE OF DELIVERY & WARRANTY	
Type of wiring	Ending	LIFETIME		Manufacturer warranty	5 years
LED rated current	350 mA	LED lifespan (25 °C)	50000 h	CERTIFICATES & EPREL	
				EPREL energy efficiency class	G

fayola MF2 On-Off/Phasecut D2W

FAYOLA MF2

Accessories

ORDERING INFORMATION	
Art.-Nr.	220445
Typ	fayola MF2 On-Off/Phasecut D2W
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	