

zwena connect HF P900 3K

ZWENA CONNECT P

neva
lux

900 x 82 mm



zwena connect HF P900 3K

ZWENA CONNECT P

Technical Data

IDENTIFICATION

Source	woocommerce
Product status	Normal
Manufacturer	Nevalux

DIMENSIONS

Dimensions Ø x H	900 x 82 mm
Suspension length	1500 mm

ELECTRICAL

Mains connection	200...240 V / 50 – 60 Hz
Power	80 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
LED rated current	2100 mA

SENSOR TECHNOLOGY

Sensor technology	High frequency
With motion detector	Yes
Detection angle	360°
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)

Mounting height < 4 m

Nevalux sensor technology	Smartlink, BT SIG Mesh
With light sensor	Yes

CONNECTIVITY

With radio network control	Yes
----------------------------	-----

LIGHTING TECHNOLOGY

Colour temperature	3000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	9000 lm (Down 5600, Up 3400)

Beam angle	Down 95°, Up 100°
Luminaire luminous efficacy	113 lm/W

Glare value	UGR < 18
-------------	----------

LIFETIME

LED lifespan (25 °C) 50000 h

SETTINGS

DALI dimming	Yes
--------------	-----

With emergency light	No emergency light
1. The first person to see the accident should call the police and ambulance. 2. If there is a fire, call the fire department. 3. If there is a traffic accident, call the traffic police. 4. If there is a medical emergency, call the ambulance. 5. If there is a fire, call the fire department. 6. If there is a traffic accident, call the traffic police. 7. If there is a medical emergency, call the ambulance. 8. If there is a fire, call the fire department. 9. If there is a traffic accident, call the traffic police. 10. If there is a medical emergency, call the ambulance.	1. The first person to see the accident should call the police and ambulance. 2. If there is a fire, call the fire department. 3. If there is a traffic accident, call the traffic police. 4. If there is a medical emergency, call the ambulance. 5. If there is a fire, call the fire department. 6. If there is a traffic accident, call the traffic police. 7. If there is a medical emergency, call the ambulance. 8. If there is a fire, call the fire department. 9. If there is a traffic accident, call the traffic police. 10. If there is a medical emergency, call the ambulance.

Direct/indirect ratio	No
separately controllable	

With program-controlled lighting control	Yes
--	-----

Constant light output control	Yes
-------------------------------	-----

HOUSING & MATERIAL

Protection class (IP)	IP20
-----------------------	------

Protection class	I
------------------	---

Ambient temperature -20...45 °C

Housing material	Aluminum
------------------	----------

Cover material	Microprismatic acrylic glass
----------------	------------------------------

Mounting type

Ceiling pendant

Colour	White
--------	-------

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
-----------------------	---------

CERTIFICATES & EPREL

EPREL energy efficiency class

zwena connect HF P900 3K

ZWENA CONNECT P

Illustrations


MOUNTING HEIGHT

< 4 m BEREICH
--

zwena connect HF P900 3K

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221618	Emergency Package 1h (50V/3.5W)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222060

Typ

zwena connect HF P900 3K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss