

zwena DALI C350 4K

ZWENA CONNECT C

neva
lux

350 x 82 mm



zwena DALI C350 4K

ZWENA CONNECT C

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No
Source	woocommerce	LIGHTING TECHNOLOGY					
Product status	Normal	Colour temperature	4000 K				
Manufacturer	Nevalux	LED colour deviation	SDCM3				
DIMENSIONS		Colour rendering index	80-89				
Dimensions Ø × H	350 x 82 mm	Illuminant	LED				
ELECTRICAL		Luminous flux	1700 lm (Down 1200, Up 500)				
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	Down 95°, Up 100°				
Power	18 W	Luminaire luminous efficacy	94 lm/W				
Replaceable driver	Yes	Glare value	UGR < 18				
Type of wiring	Suitable for through wiring	LIFETIME					
LED rated current	450 mA	LED lifespan (25 °C)	50000 h				
SENSOR TECHNOLOGY		SETTINGS					
With motion detector	No	DALI dimming	Yes				
Nevalux sensor technology	DALI 2						

Direct/indirect ratio separately controllable		No
HOUSING & MATERIAL		
Protection class (IP)	IP20	
Protection class	I	
Ambient temperature	-20...45 °C	
Housing material	Aluminum	
Cover material	Microprismatic acrylic glass	
Mounting type	Ceiling / wall surface-mounted	
Colour	White	
SCOPE OF DELIVERY & WARRANTY		
Manufacturer warranty	5 years	
CERTIFICATES & EPREL		
EPREL energy efficiency class	F	

zwena DALI C350 4K

ZWENA CONNECT C

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220572	zwena DALI C450 4K	
 220574	zwena DALI C600 4K	
 220576	zwena DALI C900 4K	
 220692	Emergency Package 1h (50V/1.5W/Compact)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220570

Typ

zwena DALI C350 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss