

RS PRO 5100 SC mit Bewegungsmelder & Bluetooth Verso

neva
lux

RS PRO 5100 UND 5150

1370 x 87 x 58 mm



RS PRO 5100 SC mit Bewegungsmelder & Bluetooth Verso

RS PRO 5100 UND 5150

Technical Data

IDENTIFICATION		Nevalux sensor technology		BT SIG Mesh	Base light function		Yes
Source	woocommerce	CONNECTIVITY			Base light function time		1-60 min
Product status	Normal	Networking		Yes	Settings via		Bluetooth
Manufacturer	Nevalux	LIGHTING TECHNOLOGY			Base light function in percent		10 %
DIMENSIONS		Measured luminous flux 360°		4250 lm	Base light function percent from		10
Dimensions L x W x H		Colour temperature		4000 K	HOUSING & MATERIAL		
ELECTRICAL		LED colour deviation		SDCM3	Impact resistance		IK07
Mains connection	220 – 240 V / 50 – 60 Hz	Colour rendering index		80-89	Protection class (IP)		IP66
Power	31 W	Illuminant		LED cannot be replaced	Protection class		II
Own consumption	0,41 W	LED cooling system		Passive Thermo Control	Ambient temperature		-20 – 40 °C
SENSOR TECHNOLOGY		LIFETIME			Housing material		Plastic
Max. mounting height	3,50 m	LED lifetime max. °C		60000 h	Cover material		Plastic, structured
Sensor technology	High frequency	LED lifetime L70B50 25°C		> 60000 h	Colour		grey
Transmission power	< 1 mW	Luminous flux decline per LM80		L80B10	SCOPE OF DELIVERY & WARRANTY		
With motion detector	Yes	SETTINGS			Manufacturer warranty		5 years
Detection angle	360 °	Twilight setting		2 – 2000 lx	CERTIFICATES & EPREL		
Opening angle	160 °	Time setting		5 sec – 60 min	Certificates		DEKRA
Electronic scalability	Yes						
Mounting height	3,5 m						

RS PRO 5100 SC mit Bewegungsmelder & Bluetooth Verso

RS PRO 5100 UND 5150

Illustrations

MOUNTING HEIGHT

3,5 m BEREICH	3,50 m MAX
------------------	---------------

RS PRO 5100 SC mit Bewegungsmelder & Bluetooth Verso

RS PRO 5100 UND 5150

Accessories

ORDERING INFORMATION

Art.-Nr. 221392

Typ **RS PRO 5100 SC mit Bewegungsmelder & Bluetooth
Verso**

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss