

nefera S V2 Connect 4K

NEFERA CONNECT S

neva
lux

726 x 310 x 1954 mm



nefera S V2 Connect 4K

NEFERA CONNECT S

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions L x W x H	726 x 310 x 1954 mm
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	80 W
Replaceable driver	Yes
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360°
Radial range	4 x 4 m (16 m²)
Tangential range	4 x 4 m (16 m²)
Presence range	4 x 4 m (16 m²)
Nevalux sensor technology	Smartlink, BT SIG Mesh

With light sensor	Yes
CONNECTIVITY	
With radio network control	Yes
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	10400 lm (Down 3850, Up 6550)
Beam angle	Down 80°, Up 115°
Luminaire luminous efficacy	130 lm/W
Glare value	UGR < 18
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes

Direct/indirect ratio separately controllable	No
With program-controlled lighting control	Yes
Constant light output control	Yes
With switch	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Microprismatic acrylic glass
Mounting type	Free standing floor
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	D

nefera S V2 Connect 4K

NEFERA CONNECT S

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221570	Connect TK2 BLM	Pushbutton interface

ORDERING INFORMATION Art.-Nr.221987 Typnefera S V2 Connect 4K	nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss
--	--