

anele connect C595

ANELE CONNECT

neva
lux

Product code **221567**

- For universal use for lighting offices, schools, traffic zones, etc.
- Available as intelligent Connect version or as conventional DALI luminaire
- Connect variant with motion detector and powerful IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Microprismatic diffuser for best possible glare control
- Variants available with 595 and 620 mm length
- Surface-mounted housing and installation springs for suspended ceilings available as accessories
- Housing Aluminium RAL9016, white

neva
lux

595 x 595 x 8.5 mm (Einbautiefe: 40 mm)



anele connect C595

ANELE CONNECT

Product code 221567

Technical Data

DIMENSIONS		CONNECTIVITY		Suitable for light band configuration	No
Dimensions L x W x H	595 x 595 x 8.5 mm (Einbautiefe: 40 mm)	With radio network control	Yes	With program-controlled lighting control	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Colour temperature	4000 K	Protection class (IP)	IP20
Power	33 W	LED colour deviation	SDCM3	Protection class	I
Replaceable driver	Yes	Colour rendering index	80-89	Ambient temperature	-20...45 °C
Type of wiring	Suitable for through wiring	Illuminant	LED	Housing material	Aluminum
SENSOR TECHNOLOGY		Luminous flux	3960 lm	Cover material	Microprismatic acrylic glass
Sensor technology	passive infrared	Beam angle	90°	Mounting type	In-ceiling installation
With motion detector	Yes	Luminaire luminous efficacy	120 lm/W	Colour	white
Detection angle	360 °	Glare value	UGR < 19	SCOPE OF DELIVERY & WARRANTY	
Radial range	4 x 4 m (16 m²)	LIFETIME		Manufacturer warranty	5 years
Tangential range	6 x 6 m (36 m²)	LED lifespan (25 °C)	50000 h	CERTIFICATES & EPREL	
Mounting height	< 10 m	SETTINGS		EPREL energy efficiency class	E
Presence range	4 x 4 m (16 m²)	DALI dimming	Yes		
With light sensor	Yes	With emergency light	No		

anele connect C595

ANELE CONNECT

Product code 221567

Illustrations

MOUNTING HEIGHT


< 10 m BEREICH

anele connect C595

ANELE CONNECT

Product code 221567

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221638	anele APG 595	Installation housing
 221639	anele APG 620	Installation housing
 221640	anele DEF	Mounting kit
 221641	anele P-Set	Suspension cable
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
		

ORDERING INFORMATION

Art.-Nr.221567

Typanele connect C595

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss