

ayana DALI P440 4K

AYANA

neva
lux

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

440 x 95 mm



ayana DALI P440 4K

AYANA

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions Ø × H	440 x 95 mm
Suspension length	2000 mm
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	43 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
SENSOR TECHNOLOGY	
With motion detector	No
Nevalux sensor technology	DALI 2, On / Off

With light sensor	No
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	5200 lm (Down 4470, Up 730)
Beam angle	105°
Luminaire luminous efficacy	121 lm/W
Glare value	UGR < 22
LIFETIME	
LED lifespan (25 °C)	70000 h
SETTINGS	
DALI dimming	Yes

With emergency light	No
Direct/indirect ratio separately controllable	No
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Steel
Cover material	Acrylic glass opal
Mounting type	Ceiling pendant
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	E

ayana DALI P440 4K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
221103	ayana Diffusor 440 CDP	Cover
221108	Emergency Package 1h (Astra)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221147

Typ

ayana DALI P440 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss