

IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR



EAN 4007841065942

- Passive infrared presence detector with square 360° detection
- 5.200 switching zones for the finest detection
- Offers the largest detection range in our IR range
- 4 pyro sensors individually de-/activatable
- Sensitivity digitally adjustable
- Measures presence and brightness
- Temperature and humidity measurement with IP, KNX and DALI-2 IPD
- Setting and networking via Bluetooth
- Ideal for open-plan offices and classrooms

64 x 123 x 123 mm



IR Quattro HD-2 24m IP - surface

EAN 4007841065942

PRESENCE DETECTOR

Technical Data

IDENTIFICATION		Sneak-under protection		Yes	Functions	Motions sensor Presence function Presence detector logic
PU1 EAN	4007841065942	Segment-by-segment masking		Yes		
Material number	110072485	Electronic scalability		Yes		
SAP designation	PRAESENZMELDER IR QUATTRO HD-2 IP AP	Mechanical scalability		Yes		
Version	Presence detector	Radial range		9 x 9 m (81 m²)	Settings via	Bluetooth Web-Interface
Product name data sheet	IR Quattro HD-2 24m IP - surface	Tangential range		24 x 24 m (576 m²)	With remote control	No
Product category	Presence detector	Mounting height		2,50 – 10,00 m	Twilight setting teach	Yes
Discount group	P1	Presence range		9 x 9 m (81 m²)	HOUSING & MATERIAL	
Source	Steinel Excel	Optimal mounting height		2,8 m	Protection class (IP)	IP20
Product status	Normal	Nevalux sensor technology		BT SIG Mesh, IP / IT	Ambient temperature	from 0 up to 40 °C
Manufacturer	Steinel	CONNECTIVITY			Mounting location	ceiling
DIMENSIONS		Networking		Yes	Application location	Indoors
Dimensions L x W x H	64 x 123 x 123 mm	Networking via		Bluetooth Mesh	Mounting type	Surface wiring
PU1 net weight	0.246	With bus coupler		Yes	Material	Plastic
ELECTRICAL		LIGHTING TECHNOLOGY			Application room	lecture hall classroom open-plan office high-bay warehouse production facilities conference room / meeting room duty room recreation room changing room reception / lobby sports hall multi-storey / underground car park dining hall / staff restaurant
Mains connection	24 – 55 V	Soft light start		No		Indoors
Own consumption	0,3 W	Continuous light		selectable	Colour	white
Supply voltage detail	Passive PoE SELV, standard PoE (IEEE 802.3 af)	Constant light regulation		No	RAL colour	9003
SENSOR TECHNOLOGY		SETTINGS			SCOPE OF DELIVERY & WARRANTY	
Max. mounting height	10,00 m	Twilight switch		Yes	Manufacturer warranty	5 years
Sensor technology	passive infrared	Twilight setting		2 – 2000 lx	Corner wall bracket included	No
Detection angle	360 °	Base light function		No		
		Main light adjustable		No		


IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN 4007841065942

Illustrations

TECHNICAL DRAWINGS



64 x 123 x 123 mm

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------


IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN 4007841065942

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

IR Quattro HD-2 24m IP - surface

EAN 4007841065942

PRESENCE DETECTOR

Highlights



UV-resistant plastic

IR Quattro HD-2 24m IP - surface

PRESENCE DETECTOR

EAN 4007841065942

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

065942

EAN

4007841065942

Typ

IR Quattro HD-2 24m IP - surface

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss