

asali connect B1500 4K 120

ASALI

neva
lux

- The universal trunking insert asali from nevalux is designed for professional refurbishment of existing trunking with T5 or T8 fluorescent tubes. The luminaire uses the existing trunking installation. Old light modules can be replaced with new modules easily, quickly and without tools. The insert fits most trunking systems available on the market. The intelligent asali Connect application variants have permanently installed presence and brightness sensors in conjunction with Bluetooth networking. This results in a powerful light management system as well as unlimited flexibility in the formation of light groups. The savings achieved in addition to the LED technology are considerable and make it possible to claim subsidies.

1528 x 64.7 x 30 mm



asali connect B1500 4K 120

ASALI

Technical Data

IDENTIFICATION				SETTINGS	
Source	woocommerce	Tangential range	6 x 6 m (36 m²)	DALI dimming	Yes
Product status	Normal	Mounting height	< 10 m	With emergency light	No
Manufacturer	Nevalux	Presence range	4 x 4 m (16 m²)	Suitable for light band configuration	Yes
DIMENSIONS		Nevalux sensor technology	Smartlink, BT SIG Mesh	With program-controlled lighting control	Yes
Dimensions L x W x H	1528 x 64.7 x 30 mm	With light sensor	Yes	HOUSING & MATERIAL	
ELECTRICAL		CONNECTIVITY		Protection class (IP)	IP40
Mains connection	200...240 V / 50 – 60 Hz	With radio network control	Yes	Protection class	I
Power	68 W	LIGHTING TECHNOLOGY		Ambient temperature	-20...45 °C
Replaceable driver	Yes	Colour temperature	4000 K	Housing material	Aluminum
Type of wiring	Through wiring included	LED colour deviation	SDCM3	Cover material	Lens transparent
LED rated current	310 mA	Colour rendering index	80-89	Mounting type	Use in continuous row
Maximum number of luminaires per circuit breaker	C10: 12x, C13: 15x, C16: 19x, C20: 24x, B10: 7x , B13: 9x, B16: 11x, B20: 14x	Illuminant	LED	Colour	White
SENSOR TECHNOLOGY		Luminous flux	10880 lm	SCOPE OF DELIVERY & WARRANTY	
Sensor technology	passive infrared	Beam angle	120°	Manufacturer warranty	5 years
With motion detector	Yes	Luminaire luminous efficacy	160 lm/W	CERTIFICATES & EPREL	
Detection angle	360°	Glare value	UGR < 26	EPREL energy efficiency class	C
Radial range	4 x 4 m (16 m²)	LIFETIME			
		LED lifespan (25 °C)	50000 h		

asali connect B1500 4K 120

ASALI

Illustrations





MOUNTING HEIGHT

< 10 m BEREICH

asali connect B1500 4K 120

ASALI

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221611	asali WAGO Male	Plug/Clamp
	221612	asali WAGO Female	Plug/Clamp
	221613	asali extension 5x 1.6	Connecting cable
	221614	asali extension 5x 3.2	Connecting cable
	221615	asali extension 7x 1.6	Connecting cable
	221616	asali extension 7x 3.2	Connecting cable
	221617	asali Blindcover	Cover
	220688	Emergency Package 1h (250V/3.5W)	Emergency lighting
ORDERING INFORMATION Art.-Nr. 221580 Typ asali connect B1500 4K 120 neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss			
	221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
	221830	asali APC1500	Surface mount housing