

IR Quattro HD-2 24m BT IPD - concealed

neva
lux

PRESENCE DETECTOR

EAN 4007841064396

- Passive infrared presence detector with square 360° detection
- 5.200 switching zones for the finest detection
- Offers the largest detection range in our IR range
- 4 pyro sensors individually de-/activatable
- Sensitivity digitally adjustable
- Measures presence and brightness
- Temperature and humidity measurement with IP, KNX and DALI-2 IPD
- Setting and networking via Bluetooth
- Ideal for open-plan offices and classrooms

69 x 103 x 103 mm



IR Quattro HD-2 24m BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841064396

Technical Data

IDENTIFICATION	
PU1 EAN	4007841064396
Material number	110067701
SAP designation	PRAESENZMELDER IR Q HD-2 BT-IPD UP WS
Version	Presence detector
Product name data sheet	IR Quattro HD-2 24m BT IPD - concealed
Product category	Presence detector
Discount group	P1
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel
DIMENSIONS	
Dimensions L x W x H	69 x 103 x 103 mm
PU1 net weight	0.142
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Own consumption	0,3 W
SENSOR TECHNOLOGY	
Max. mounting height	10,00 m
Sensor technology	passive infrared
Detection angle	360 °
Opening angle	160 °

Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	Yes
Radial range	9 x 9 m (81 m²)
Tangential range	24 x 24 m (576 m²)
Switching zones	5200 switching zones
Mounting height	2,50 – 10,00 m
Presence range	9 x 9 m (81 m²)
Optimal mounting height	2,8 m
Nevalux sensor technology	BT SIG Mesh
CONNECTIVITY	
Networking	Yes
Networking via	Bluetooth Mesh
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	No

Main light adjustable	No
Settings via	Bluetooth
With remote control	No
Twilight setting teach	No
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	lecture hall classroom open-plan office high-bay warehouse production facilities conference room / meeting room duty room recreation room changing room reception / lobby sports hall multi-storey / underground car park dining hall / staff restaurant Indoors
Colour	white
RAL colour	9003
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro HD-2 24m BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841064396

Illustrations

TECHNICAL DRAWINGS



69 x 103 x 103 mm

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------


IR Quattro HD-2 24m BT IPD - concealed

EAN 4007841064396

PRESENCE DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

IR Quattro HD-2 24m BT IPD - concealed

EAN 4007841064396

PRESENCE DETECTOR

Highlights



UV-resistant plastic

IR Quattro HD-2 24m BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841064396

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

064396

EAN

4007841064396

Typ

IR Quattro HD-2 24m BT IPD - concealed

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss