

asali B1500 4K DALI 120

ASALI

neva
lux

- The universal trunking insert asali from nevalux is designed for professional refurbishment of existing trunking with T5 or T8 fluorescent tubes. The luminaire uses the existing trunking installation. Old light modules can be replaced with new modules easily, quickly and without tools. The insert fits most trunking systems available on the market.

1528 x 64.7 x 30 mm



asali B1500 4K DALI 120

ASALI

Technical Data

IDENTIFICATION			
Source	woocommerce	Nevalux sensor technology	DALI 2
Product status	Normal	With light sensor	No
Manufacturer	Nevalux	LIGHTING TECHNOLOGY	
DIMENSIONS		Colour temperature	4000 K
Dimensions L x W x H	1528 x 64.7 x 30 mm	LED colour deviation	SDCM3
ELECTRICAL		Colour rendering index	80-89
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED
Power	68 W	Luminous flux	10880 lm
Replaceable driver	Yes	Beam angle	120°
Type of wiring	Through wiring included	Luminaire luminous efficacy	160 lm/W
LED rated current	310 mA	Glare value	UGR < 26
Maximum number of luminaires per circuit breaker	C10: 15x, C16: 24x, C25: 37x, B10: 9x , B16: 14x, B25: 22x	LIFETIME	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h
With motion detector	No	SETTINGS	
		DALI dimming	Yes
		With emergency light	No
		Suitable for light band configuration	Yes
		HOUSING & MATERIAL	
		Protection class (IP)	IP40
		Protection class	I
		Ambient temperature	-20...45 °C
		Housing material	Aluminum
		Cover material	Lens transparent
		Mounting type	Use in continuous row
		Colour	White
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		CERTIFICATES & EPREL	
		EPREL energy efficiency class	C

asali B1500 4K DALI 120

ASALI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221611	asali WAGO Male	Plug/Clamp
 221612	asali WAGO Female	Plug/Clamp
 221613	asali extension 5x 1.6	Connecting cable
 221614	asali extension 5x 3.2	Connecting cable
 221615	asali extension 7x 1.6	Connecting cable
 221616	asali extension 7x 3.2	Connecting cable
 221617	asali Blindcover	Cover
 220688	Emergency Package 1h (250V/3.5W)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.221609

Typasali B1500 4K DALI 120

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss