

# elani C3200 4K

ELANI

neva  
lux

3140 x 60 x 80 mm



elani C3200 4K

ELANI

Technical Data

| IDENTIFICATION            |                             | LIGHTING TECHNOLOGY         |                 | Suitable for light band configuration | Yes                            |
|---------------------------|-----------------------------|-----------------------------|-----------------|---------------------------------------|--------------------------------|
| Source                    | woocommerce                 | Colour temperature          | 4000 K          |                                       |                                |
| Product status            | Normal                      | LED colour deviation        | SDCM3           | HOUSING & MATERIAL                    |                                |
| Manufacturer              | Nevalux                     | Colour rendering index      | 80-89           | Protection class (IP)                 | IP20                           |
| DIMENSIONS                |                             | Illuminant                  | Yes, LED-System | Protection class                      | II                             |
| Dimensions L x W x H      | 3140 x 60 x 80 mm           | Luminous flux               | 8792 lm         | Ambient temperature                   | -20...45 °C                    |
| ELECTRICAL                |                             | Beam angle                  | 105°            | Housing material                      | Aluminium                      |
| Mains connection          | 200...240 V / 50 – 60 Hz    | Luminaire luminous efficacy | 112 lm/W        | Cover material                        | Acrylic glass opal             |
| Power                     | 78,5 W                      | Glare value                 | UGR < 24        | Mounting type                         | Ceiling / wall surface-mounted |
| Replaceable driver        | Yes                         | LIFETIME                    |                 | Colour                                | Aluminium                      |
| Type of wiring            | Suitable for through wiring | LED lifespan (25 °C)        | 50000 h         | SCOPE OF DELIVERY & WARRANTY          |                                |
| SENSOR TECHNOLOGY         |                             | SETTINGS                    |                 | Manufacturer warranty                 | 5 years                        |
| With motion detector      | No                          | DALI dimming                | Yes             | CERTIFICATES & EPREL                  |                                |
| Nevalux sensor technology | DALI 2                      | With emergency light        | No              | EPREL energy efficiency class         | E                              |
| With light sensor         | No                          |                             |                 |                                       |                                |

elani C3200 4K

ELANI

Accessories

| ARTICLE NUMBER                                                                            | DESCRIPTION                  | CATEGORY                   |
|-------------------------------------------------------------------------------------------|------------------------------|----------------------------|
|  221102   | elani Diffusor 3200 CDP      | Cover                      |
|  221108   | Emergency Package 1h (Astra) | Emergency lighting         |
|  221343   | elani Connector 90°          | Coupler/connector L-shape  |
|  221397  | elani Color RAL_NCS_3200     | Other                      |
|  221107 | elani Link                   | Coupler/connector straight |
|  221997 | elani WM-Set 3B              | Mounting kit               |

ORDERING INFORMATION

Art.-Nr.

221141

Typ

elani C3200 4K

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss