

True Presence COM2 - surface white

PRESENCE DETECTOR

neva
lux

EAN 4007841057930

45 x 123 x 123 mm



True Presence COM2 - surface white

PRESENCE DETECTOR

EAN 4007841057930

Technical Data

IDENTIFICATION

PU1 EAN	4007841057930
Material number	110062729
SAP designation	PRAESENZMELDER TRUE PRESENCE COM2 AP WS
Version	Presence detector
Product name data sheet	True Presence COM2 - surface white
Product category	Presence detector
Discount group	TP
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel

DIMENSIONS

Dimensions L x W x H	45 x 123 x 123 mm
PU1 net weight	0.279

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	2000 W
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	1000 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in μF	176 μF
Own consumption	1 W
Switching output 1 number of LED/fluorescent lamps	8
Switching output 1 potential-free	No

Switching output 2 resistive	230 W
Switching output 2 potential-free	Yes
Maximum inrush current	800 A

SENSOR TECHNOLOGY

Max. mounting height	12,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	7,2 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 15 m (177 m²)
Tangential range	Ø 15 m (177 m²)
Mounting height	2,00 – 12,00 m
Presence range	Ø 15 m (177 m²)
True Presence range	Ø 9 m (64 m²)
Optimal mounting height	2,8 m
Max. mounting height True Presence detection	4,00 m
Nevalux sensor technology	BT Open Mesh, On / Off

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave
Networking via	Bluetooth

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable

Constant light regulation	No
---------------------------	----

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	20 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Group parameterisation Semi-/fully automatic Lighting scenario Manual ON / ON-OFF Neighbouring group function Normal / test mode
Settings via	Bluetooth
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP54
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Application room	classroom lecture hall one-person office open-plan office high-bay warehouse production facilities conference room / meeting room hotel room care room duty room recreation room dining hall / staff restaurant changing room kitchenette sports hall reception / lobby WC / washroom warehouse
	Indoors

Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


True Presence COM2 - surface white

PRESENCE DETECTOR

EAN 4007841057930

Illustrations

TECHNICAL DRAWINGS



45 x 123 x 123 mm

MOUNTING HEIGHT

2,00 – 12,00 m BEREICH	2,8 m OPTIMAL	12,00 m MAX
---------------------------	------------------	----------------


True Presence COM2 - surface white

EAN 4007841057930

PRESENCE DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

True Presence COM2 - surface white


EAN 4007841057930

PRESENCE DETECTOR


Highlights



UV-resistant plastic



Digital high frequency sensor



Interconnectable and adjustable via
Bluetooth

True Presence COM2 - surface white

EAN 4007841057930

PRESENCE DETECTOR

Accessories

ORDERING INFORMATION

Art.-Nr. 057930

EAN 4007841057930

Typ True Presence COM2 - surface white

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss