

IS 345 DALI-2 APC - surface, rd.

MOTION DETECTOR

neva
lux

EAN 4007841033859

126 x 65 mm



IS 345 DALI-2 APC - surface, rd.

MOTION DETECTOR

EAN 4007841033859

Technical Data

IDENTIFICATION					
PU1 EAN	4007841033859	Electronic scalability	No	Settings via	Remote control
Material number	110046127	Mechanical scalability	No		Potentiometers Smart Remote
SAP designation	BEWEGUNGSMELDER IS 345-R DALI AP WS	Radial range	12 x 6 m (72 m²)	With remote control	No
Version	Motion detectors	Tangential range	23 x 6 m (138 m²)	Twilight setting teach	Yes
Product name data sheet	IS 345 DALI-2 APC - surface, rd.	Switching zones	280 switching zones	Base light function in percent	10 – 50 %
Product category	Motion detector	Mounting height	2,50 – 5,00 m	Base light function percent from	10
Discount group	B	Optimal mounting height	2,8 m	Base light function percent to	50
Source	Steinel Excel	Nevalux sensor technology	DALI 2	HOUSING & MATERIAL	
Product status	Normal	CONNECTIVITY		Protection class (IP)	IP54
Manufacturer	Steinel	Networking	Yes	Ambient temperature	from -20 up to 50 °C
DIMENSIONS		Type of networking	Master/slave	Mounting location	ceiling
Dimensions Ø × H	126 x 65 mm	Networking via	Cable	Application location	Outdoors Indoors
PU1 net weight	0.17	LIGHTING TECHNOLOGY		Mounting type	Surface wiring
ELECTRICAL		Soft light start	Yes	Material	Plastic
Mains connection	220 – 240 V / 50 – 60 Hz	Continuous light	selectable, 4h	Application room	corridor / aisle multi-storey / underground car park outdoors Indoors
Control output DALI	Broadcast 1x30 electronic ballasts	Constant light regulation	Yes	Colour	white
SENSOR TECHNOLOGY		SETTINGS		RAL colour	9003
Max. mounting height	5,00 m	Twilight switch	Yes	SCOPE OF DELIVERY & WARRANTY	
Sensor technology	passive infrared	Twilight setting	2 – 1000 lx	Manufacturer warranty	5 years
Detection angle	360 °	Time setting	5 s – 15 Min.	Corner wall bracket included	No
Opening angle	45 °	Base light function	Yes	CERTIFICATES & EPREL	
Sneak-under protection	Yes	Base light function time	1-30 min all night	Certificates	DALI-2
Segment-by-segment masking	Yes	Main light adjustable	50 - 100 %		
		Functions	Normal / test mode Manual ON / ON-OFF Constant-lighting control ON-OFF		


IS 345 DALI-2 APC - surface, rd.

MOTION DETECTOR

EAN 4007841033859

Illustrations

TECHNICAL DRAWINGS



126 x 65 mm

MOUNTING HEIGHT

2,50 – 5,00 m BEREICH	2,8 m OPTIMAL	5,00 m MAX
--------------------------	------------------	---------------


IS 345 DALI-2 APC - surface, rd.

MOTION DETECTOR

EAN 4007841033859


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Circuit diagram for interconnecting DALI-2 APC with DALI-2 IPD

IS 345 DALI-2 APC - surface, rd.


EAN 4007841033859

MOTION DETECTOR

Highlights



UV-resistant plastic



Large terminal compartment



Optional remote controls

IS 345 DALI-2 APC - surface, rd.

MOTION DETECTOR

EAN 4007841033859

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841056735	Schwarze Blende für IR-Sensoren Aufputz rund	Accessory

ORDERING INFORMATION

Art.-Nr.

033859

EAN

4007841033859

Typ

IS 345 DALI-2 APC - surface, rd.

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss