

PD IR 4360-8 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

neva
lux

EAN 4007841085117

- Our series for the common ranges
- Presence detector with 8 m motion detection and 6 m presence detection for switching light
- Ideal for offices, meeting rooms or passageways
- Includes insertable cover caps to limit the detection range
- Installation-friendly, thanks to round design and modular system with magnetic plug-in connection
- Key input and parallel switching of multiple sensors to expand the detection range
- External approval and measurement in accordance with sensNORM

109 x 69 mm



PD IR 4360-8 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085117

Technical Data

IDENTIFICATION			
PU1 EAN	4007841085117	Sensor technology	passive infrared
Material number	110090129	With motion detector	Yes
SAP designation	PRAESENZMELDER PD IR 4360-8 COM1 UP SW	Detection angle	360 °
Version	Motion and Presence Detector	Sneak-under protection	Yes
Product name data sheet	PD IR 4360-8 COM1 - concealed black	Segment-by-segment masking	Yes
Product category	Motion and Presence Detector	Electronic scalability	No
Discount group	P	Mechanical scalability	No
Source	Steinel Excel	Radial range	Ø 4.5 m (16 m²)
Product status	Normal	Tangential range	Ø 8 m (50 m²)
Manufacturer	Steinel	Switching zones	492 switching zones
DIMENSIONS		Mounting height	2 – 4 m
Dimensions Ø × H	109 x 69 mm	Presence range	Ø 6 m (28 m²)
PU1 net weight	0.167	Optimal mounting height	2,8 m
ELECTRICAL		Nevalux sensor technology	On / Off
Mains connection	50 – 60 Hz	CONNECTIVITY	
Switching output 1 resistive	2000 W	Networking	Yes
LED lamps > 8 W	500 W	Type of networking	Master/master
Capacitive load in µF	176 µF	Networking via	Cable
Switching output 1 number of LED/fluorescent lamps	50	LIGHTING TECHNOLOGY	
Maximum inrush current	800 A	Soft light start	Yes
SENSOR TECHNOLOGY		Constant light regulation	No
Max. mounting height	4,00 m	SETTINGS	
		Twilight switch	Yes
		Twilight setting	2 – 1000 lx
		Time setting	5 s – 60 Min.
		Main light adjustable	No
		Functions	Motions sensor Light sensor Presence function Presence detector logic Semi-/fully automatic Potentiometer Relay output Normal / test mode
		Settings via	Remote control Smart Remote Potentiometers
		With remote control	No
		Twilight setting teach	Yes
		HOUSING & MATERIAL	
		Protection class (IP)	IP20
		Ambient temperature	from -20 up to 50 °C
		Housing material	Plastic
		Cover material	Other
		Cover material (scope of delivery)	shrouds
		Mounting location	ceiling
		Application location	Indoors
		Mounting type	Concealed wiring
		Material	Plastic
		Application room	one-person office function room / ancillary room Indoors warehouse
		Colour	black
		RAL colour	9010
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		Corner wall bracket included	No

PD IR 4360-8 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085117

Illustrations

TECHNICAL DRAWINGS



109 x 69 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------	------------------	---------------

PD IR 4360-8 COM1 - concealed black

EAN 4007841085117

MOTION AND PRESENCE DETECTOR


Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

WIRING DIAGRAM 2



Circuit diagram for interconnecting max. 10 sensors

PD IR 4360-8 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085117

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841079543	Deckeneinbau-Adapter Deckeneinbau	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

085117

EAN

4007841085117

Typ

PD IR 4360-8 COM1 - concealed black

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss