

aluna connect LS P630 4K

ALUNA

neva
lux

630 x 118 mm



aluna connect LS P630 4K

ALUNA


Technical Data

IDENTIFICATION		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Source	woocommerce	With radio network control	Yes	With program-controlled lighting control	Yes
DIMENSIONS		LIGHTING TECHNOLOGY		Constant light output control	Yes
Product status	Normal	Colour temperature	4000 K	HOUSING & MATERIAL	
Manufacturer	Nevalux	LED colour deviation	SDCM3	Protection class (IP)	IP20
ELECTRICAL		Colour rendering index	80-89	Protection class	I
Dimensions Ø × H	630 x 118 mm	Illuminant	LED	Ambient temperature	-20...45 °C
Suspension length	2000 mm	Luminous flux	6100 lm (Down 5250, Up 850)	Housing material	Steel
SENSOR TECHNOLOGY		Beam angle	105°	Cover material	Acrylic glass opal
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	120 lm/W	Mounting type	Ceiling pendant
Power	51 W	Glare value	UGR < 21	Colour	White
Replaceable driver	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	70000 h	Manufacturer warranty	5 years
SETTINGS		CERTIFICATES & EPREL		EPREL energy efficiency class	E
With motion detector	No	DALI dimming	Yes		
Nevalux sensor technology	Smartlink, BT SIG Mesh	With emergency light	No		
With light sensor	Yes				

aluna connect LS P630 4K

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221104	ayana Diffusor 570 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221845	aluna Color RAL_NCS_0630	Other
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222034

Typ

aluna connect LS P630 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss