

nefera C120 4K

NEFERA C / P / W

neva
lux

1200 x 260 x 30 mm



nefera C120 4K

NEFERA C / P / W

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No
Source	woocommerce	LIGHTING TECHNOLOGY			HOUSING & MATERIAL		
Product status	Normal	Colour temperature	4000 K		Protection class (IP)	IP20	
Manufacturer	Nevalux	LED colour deviation	SDCM3		Protection class	I	
DIMENSIONS		Colour rendering index	80-89		Ambient temperature	-20...45 °C	
Dimensions L x W x H	1200 x 260 x 30 mm	Illuminant	LED		Housing material	Aluminum	
ELECTRICAL		Luminous flux	5400 lm (Down 4200, Up 1200)		Cover material	Microprismatic acrylic glass	
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	Down 90°, Up 110°		Mounting type	Ceiling surface-mounted	
Power	60 W	Luminaire luminous efficacy	90 lm/W		Colour	White	
Replaceable driver	Yes	Glare value	UGR < 19		SCOPE OF DELIVERY & WARRANTY		
Type of wiring	Suitable for through wiring	LIFETIME			Manufacturer warranty	5 years	
LED rated current	1500 mA	LED lifespan (25 °C)	50000 h		CERTIFICATES & EPREL		
SENSOR TECHNOLOGY		SETTINGS			EPREL energy efficiency class	F	
With motion detector	No	DALI dimming	Yes				
Nevalux sensor technology	DALI 2						

nefera C120 4K

NEFERA C / P / W

Accessories

ORDERING INFORMATION	
Art.-Nr.	220173
Typ	nefera C120 4K
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	