

aluna DALI P630 TW

ALUNA

neva
lux

- Timeless simple textile lamp in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight
- Fabric shade can be ordered in any color

630 x 118 mm



aluna DALI P630 TW

ALUNA


Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No		
Source	woocommerce	LIGHTING TECHNOLOGY						Direct/indirect ratio separately controllable	No
Product status	Normal	Colour temperature	3000...5600 K						
Manufacturer	Nevalux	LED colour deviation	SDCM3						
DIMENSIONS		Colour rendering index	80-89						
Dimensions Ø × H	630 x 118 mm	Illuminant	LED						
Suspension length	2000 mm	Luminous flux	6100 lm (Down 5250, Up 850)						
ELECTRICAL		Beam angle	105°						
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	120 lm/W						
Power	51 W	Glare value	UGR < 21						
Replaceable driver	Yes	LIFETIME							
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	70000 h						
SENSOR TECHNOLOGY		SETTINGS							
With motion detector	No	DALI dimming	Yes						
Nevalux sensor technology	DALI 2, On / Off								

aluna DALI P630 TW

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221104	ayana Diffusor 570 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221845	aluna Color RAL_NCS_0630	Other

ORDERING INFORMATION

Art.-Nr.

221418

Typ

aluna DALI P630 TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss