

ayana connect LS C440 4K

AYANA

neva
lux

440 x 95 mm



ayana connect LS C440 4K

AYANA

Technical Data

IDENTIFICATION		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Source	woocommerce	With radio network control	Yes	With program-controlled lighting control	Yes
DIMENSIONS		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Dimensions Ø × H	440 x 95 mm	Colour temperature	4000 K	Protection class (IP)	IP20
ELECTRICAL		LED colour deviation	SDCM3	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	Ambient temperature	-20...45 °C
Power	43 W	Illuminant	LED	Housing material	Steel
Replaceable driver	Yes	Luminous flux	5200 lm (Down 4470, Up 730)	Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	Beam angle	105°	Mounting type	Ceiling / wall surface-mounted
SENSOR TECHNOLOGY		Luminaire luminous efficacy	122 lm/W	Colour	White
With motion detector	No	Glare value	UGR < 22	SCOPE OF DELIVERY & WARRANTY	
Nevalux sensor technology	Smartlink, BT SIG Mesh	LIFETIME		Manufacturer warranty	5 years
With light sensor	Yes	LED lifespan (25 °C)	70000 h	CERTIFICATES & EPREL	
		SETTINGS		EPREL energy efficiency class	E
		DALI dimming	Yes		
		With emergency light	No		

ayana connect LS C440 4K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221103	ayana Diffusor 440 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222004

Typ

ayana connect LS C440 4K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss